



ZKL 3000 RC V2

- Protects a section of a track by simulating a train in section.
- Can be configured, controlled and monitored through the cloud platform MTinfo 3000 and MTinfo 3000 app.




IP	SIL	Communication	Operating temperature	Dimensions (mm) l x w x h	Weight
IP67	4	2G	-25 to +70 °C	870x215x114	10.6kg

Back-up battery ZKL 3000 RC




IP	Battery type	Voltage (V)	Capacity (Wh)	Dimensions (mm) l x w x h	Weight	Operating temperature (charging)	Operating temperature (discharging)
IP67	Lithium-ion	6.4	19.2	185 x 30 x 30	417g	0 to +45 °C	0 to +45 °C

External battery ZKL 3000 RC




IP	Battery type	Voltage (V)	Capacity (Wh)	Dimensions (mm) l x w x h	Weight	Operating temperature (charging)	Operating temperature (discharging)
IP67	Lithium-ion	6.4	576	2450 x 2670 x 1630	7700g	0 to +45 °C	-20 to +60 °C

Charger back-up battery ZKL 3000 RC



IP	AC input (VAC)	DC output	Operating temperature	Storage temperature	Plug
IP20	AC100-240V	7.3V (2A)	-20 to +60 °C	-40 to +85 °C	CEE 7/16

Charger external battery ZKL 3000 RC



IP	AC input (VAC)	DC output	Operating temperature	Storage temperature	Plug
IP20	AC180-240V	7.5V (6A)	-20 to +50 °C	-40 to +70 °C	CEE 7/16